

PRODUCT NAME

NON-WOVEN GEOTEXTILE POLYESTER (700GSM)
 -Mechanically bonded and needle punched

DESCRIPTION

Geotextile made from staple fibres that are mechanically bonded by a needle punching process to produce a dimensionally stable network. The fibres used are 100% virgin white Polypropylene, ultra-violet resistant with 165°C melting point.

APPLICATIONS

- Geotextiles are used in road and railway soil stabilization, waterways and seashore erosion control, asphalt pavement overlay crack relief, subsurface drainage systems, waterproofing membrane protection, landfill, landscaping etc.
- Separation between two dissimilar materials so that the integrity and functioning of both materials can remain intact or be improved.
- Filtration by permitting water flow across the plane of the geotextile while retaining fine soil particles.
- Transmission by providing water drainage and gas venting within the plane of the geotextile.
- Sealing when impregnated with asphalt or resin to act as a moisture barrier.
- Stress Absorption in pavement overlay when impregnated with asphalt.
- Protection of geo-membrane against puncture by absorbing the point stresses.

SPECIFICATIONS

PROPERTY	VALUE
Density	700GSM
Thickness	4.0MM
Wide Width Tensile Strength	30KN/m
Tensile Elongation	70%
Puncture Strength	5000N
Water Flow Rate	100L/m2/sec
AOS (O ₉₅)	80MICRONS
Melting Temperature	230°C

Head Office: 28, Strand Road, 3rd Floor, Kolkata - 700001

Corporate Office: Gajraj Chambers, 86B/2, Topsia Road (S), Suite: 1F, Kolkata - 700046

Branch-Gujarat: Gram Panchayat No 1595, Godown No - 11, Anand Estate, Ahmedabad - 382427

Branch-Chennai: Ground Floor, B-8, CMDA Truck Terminal Complex, GNT Road, Madhavaram - 600100

Phone: +91 33 4006 2040 | **Email:** info@imperialoverseas.in | **Website:** www.imperialoverseas.in